Safety Data Sheet

Davis Manufacturing



EarMed Ear Powder

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: EarMed Ear Powder

SDS Number: 1055 Product Code: EP

Revision Date: 08/12/2019

Version:

CAS Number: Contains CAS #112926-00-8

EPA Number: Not Applicable

Chemical Family: Amorphous Precipitated Silica

Product Use: Pet Ear Powder

Supplier Details: Davis Manufacturing

541 Proctor Avenue Scottdale, GA 30079

Contact: Emergency Contact: Chem-Tel 800 255-3924

 Phone:
 404 292-2424

 Fax:
 404 292-3049

 Email:
 mail@davismfg.com

 Web:
 www.davismfg.com

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

No GHS Classifications Indicated

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: NONE

GHS Hazard Pictograms:

No GHS pictograms indicated for this product

GHS Hazard Statements:

No GHS hazards statements indicated

GHS Precautionary Statements:

No GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes, Moderate; Skin, Moderate; Inhalation, Moderate, Ingestion, Low

Target Organs: Airways; Eyes; Respiratory system; Skin;

In case product dust is released, possible discomfort, cough, sneezing. If affected, remove to fresh air.

Skin Contact:

Wash off with mild soap and plenty of water. Use of super fatted soaps and skin cream may be helpful.

Eye Contact:

In case of contact with eyes, immediately flush eyes with plenty of water. Obtain medical attention if irritation

develops.

Ingestion: If accidentally swallowed, rinse mouth thoroughly with water and afterwards, drink plenty of water. In case of

discomfort, obtain medical attention.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
112926-00-8	100%	Amorphous Precipitaded Silica

A new CAS #, 112926-00-8 has been assigned-Amorphous Precipitated Silica-distinguish it from crystalline. It meets TSCA requirements and is listed on the TSCA Inventory as silica, CAS #7631-86-9.

4 FIRST AID MEASURES

In case product dust is released, possible discomfort, cough, sneezing may result. Take affected persons out into the

fresh air.

Skin Contact: Wash off skin with soap and plenty of water. Use of supper fatted soaps and skin cream may be helpful.

Eye Contact: In case of contact witth eyes, immediately flush eyes with plenty of water. Obtain medical attention if irritation develops.

In case of contact witth eyes, immediately flush eyes with plenty of water. Obtain medical attention if irritation develops.

If accidentally swallowed, rinse mouth thoroughly with water and afterwards, drink plenty of water. In case of discomfort,

obtain medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: N/A
Flash Point Method: N/A

All extinguishing substances suitable.

Take precautionary measures against static discharges. Fight the surrounding fire

6 ACCIDENTAL RELEASE MEASURES

Wear appropriate Personal Protective Equipment. Vacuum or sweep the material into a bag or other sealed container and dispose in accordance with local requirements. Do not contaminate any lakes, streams, rivers, groundwater or soils.

7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing excess dust; use with adequate ventilation

To insure ideal skin protection, use super fatted soaps and skin cream for skin care. Consider normal working hygiene. Avoid contact with eyes or skin. Keep material out of reach of children. Do not eat,

drink or smoke while using product.

Storage Requirements: Store in original, closed container. Store in cool/dry area. Keep away from children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation may be necessary.

Personal Protective Chemical resistant gloves; Chemical goggles;

Equipment: In poorly ventilated areas, you may use a NIOSH/OSHA approved dust respirator.

Time Weighted Average(TWA) 20 millions of particles per cubic foot of air

TWA ACGIH 10 mg/m3 inhalable particles TWA ACGHI 3 mg/m3 respirable particles

Permissible Exposure Limit (PEL)
PEL OSHA 5 mg/m3 respirable fraction
PEL OSHA 15 mg/m3 total dust

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White Powder

Physical State:PowderOdor:OdorlessOdor Threshold:N/ASolubility:Hardly Soluble

Spec Grav./Density:N/AFreezing/Melting Pt.:N/AViscosity:N/AFlash Point:N/ABoiling Point:N/AVapor Density:N/A

SDS Number: 1055 Page: 2 / 3 Revision Date: 08/12/2019

Partition Coefficient: N/A
Vapor Pressure: N/A
pH: 6.5

Auto-Ignition Temp: N/A **UFL/LFL:** N/A

Evap. Rate: N/A
Decomp Temp: N/A

10 STABILITY AND REACTIVITY

Conditions to Avoid: None known Materials to Avoid: None known

Hazardous Decomposition: None known for product.

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

Inhalation: LCO Rat: 0.139 mg/1/4 h No irreversible changes and no indication of silicosis

12 ECOLOGICAL INFORMATION

May be harmful to fish and aquatic life

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with prevailing local, state and federal regulations.

14 TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations

15 REGULATORY INFORMATION

R 36/37 Irritating to eyes and respiratory system.

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances

PA = PA Right-To-Know List of Hazardous Substances

16 OTHER INFORMATION

BE SAFE: READ OUR PRODUCT SAFETY INFORMATION AND PASS IT ON.

Product liability law requires it. The information provided in this Safety Data Sheet has been obtained from current sources believed to be reliable. The manufacturer provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein. This information is offered for your information, consideration and investigation. You should satisfy yourself that you have all current data relevant to your particular use.

Revision Date: 08/12/2019

SDS Number: 1055 Page: 3 / 3 Revision Date: 08/12/2019