Davis Manufacturing



Studio Color Playful Pink

| 1 | PRODUCT AND COMPANY IDENTIFICATION |
|---------------------|--|
| Product Identifier: | Studio Color Playful Pink |
| SDS Number: | DAV1233 |
| Product Code: | SCPP |
| Revision Date: | 10/22/2018 |
| Version: | 1 |
| CAS Number: | Contains CAS #64-17-5 |
| EPA Number: | Not Applicable |
| Chemical Family: | Alcohols |
| Product Use: | Pet Hair Color |
| Supplier Details: | Davis Manufacturing 541 Proctor Avenue Scottdale, GA 30079 |
| Contact: | Emergency Contact: Chem-Tel 800 255-3924 |
| Phone: | 404 292-2424 |
| Fax: | 404 292-3049 |
| Email: | mail@davismfg.com |
| Web: | www.davismfg.com |

Emergency Phone for USA: 1 800 255-3924 Emergency Phone for International: +011 813 248-0585 Service for products with hazardous items provided for Davis by Chem-Tel Inc Under Contract # MIS0001878

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 3 Health, Respiratory or skin sensitization, 1 Respiratory Health, Serious Eye Damage/Eye Irritation, 2 B

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

Flammable liquid and vapour May cause allergy or asthma symptoms of breathing difficulties if inhaled H320 - Causes eye irritation

GHS Precautionary Statements:

- P102 Keep out of reach of children.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P103 Read label before use.
- P262 Do not get in eyes, on skin, or on clothing.
- P301 IF SWALLOWED: _
- P311 Call a POISON CENTER or doctor/physician.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

| • | |
|-----------------------------------|---|
| Ingestion: | Aspiration into lungs may cause pneumonititis. For external use; may cause irritation if swallowed and large amounts may cause serious harm. |
| Eye Contact: | Direct contact with eyes may cause irritation, pain or possible corneal damage. Exposure to excessive vapors may cause irritation. |
| Skin Contact: | May cause irritation. Repeated or prolonged contact may result in defatting, redness, itching or inflammation. Skin may become discolored upon contact with the dye. |
| Inhalation: | May irritate the respiratory tract and mucous membranes. Excessive inhalation of vapors can cause central nervous sysem depression with dizziness, headache, incoordination, drowsiness or fatigue. |
| Route of Entry: Target Organs: | Inhalation: Moderate; Ingestion: High; Eyes: Moderate; Skin: Moderate Gastrointestinal tract; Digestive System; Cental nervous system; Eyes; Respiratory Tract, Skin; Lungs; |
| | |

3

5

COMPOSITION/INFORMATION OF INGREDIENTS

| | Chemical I | ngredients |
|------------|------------|---|
| CAS# | % | Chemical Name |
| 64175 | 45-49% | Ethanol |
| 18472-87-2 | <4% | Spiro[isobenzofuran-1(3H),9'- [9H]xanthen]-3-one, 2',4',5',7'- tetrabromo-4,5,6,7-tetrachloro-3',6'- dihydroxy-, disodium salt |

4 FIRST AID MEASURES

| Inhalation: Skin Contact: | If symptoms develop, move person to fresh air & if symptoms persist, consult a physician. If signs of irritation, wash with mild soap and water. |
|------------------------------|---|
| Eye Contact: | Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Seek medical attention if symptoms persist. |
| Ingestion: | If person is fully conscious, give 2 glasses of water. Induce vomiting; this should be done by experienced first aid personnel or with the advice of medical personnel. Obtain medical attention without delay. |

FIRE FIGHTING MEASURES

Flammability:Flammable LiquidFlash Point:80 F (26.6 C)Flash Point Method:Tag Closed Cup

Extinguishing Media: Carbon Dioxide, Dry Chemical or Foam

Firefighters should use self-contained breathing apparatus and protective clothing.

Unusual Fire & Explosion Hazards: Vapors may travel or move by air currents to an ignition source and flash back. Dangerous when exposed to flame or extreme heat.

6 ACCIDENTAL RELEASE MEASURES

Shut off ignition sources, no smoking. Take up with sand or other noncombustible absorbant material and place in container for later disposal.

| | HANDLING AND STORAGE |
|-----------------------|--|
| Handling Precautions: | Do not swallow. Keep away from heat, sparks and flames. Keep away from children. Avoid excessive vapors. Do not get in eyes, Product may discolor skin. Keep container closed. Use with adequate ventilation. Vapors from this may travel or be moved by air currents and ignited by pilot lights, other flames, smoking sparks, heaters static discharges or other ignition sources at locations distant from product handling area and may flashback. Wash after handling. Store at normal ambient temperatures. |
| Storage Requirements: | Store in original, closed container. Keep away from heat, sparks, and flames. Keep away from children. |
| 8 | EXPOSURE CONTROLS/PERSONAL PROTECTION |

Engineering Controls: Normal room ventilation

| 9 | PHYSICAL AND CHEMICAL PROPERTIES |
|---|--|
| Appearance: Physical State: Flammability: pH: | Reddish LiquidOdor:Alcohol OdorLiquidOdor:Solubility:Not availableFlammable LiquidSolubility:Not available4.0 - 5.0Solubility:Solubility: |
| 10 | STABILITY AND REACTIVITY |
| Chemical Stability: Conditions to Avoid: Materials to Avoid: Hazardous Decompositi | Product is stable under normal conditions. Avoid extreme heat, sparks and flames Oxidizing Agents Strong Acids; Strong Bases Burning can produce the following products: Carbon monoxide and/or carbon dioxide. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant. |
| Hazardous Polymerizati | on: Will not occur. |

| 11 | TOXICOLOGICAL INFORMATION |
|----|---------------------------|
|----|---------------------------|

Unknown for mixture

| 12 | ECOLOGICAL INFORMATION |
|----|------------------------|
| 12 | |

Unknown for mixture

Dispose of in accordance with prevailing local, state and federal regulations.

14 TRANSPORT INFORMATION

DOT Shipping Name: UN1170 Ethanol Solution 3, PGIII (In smaller quantities or sizes may be Limited Quantity or Consumer Commodity, ORM-D)

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Ethanol (64175) [45-49%] MASS, OSHAWAC, PA, TSCA, TXAIR

Spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one, 2',4',5',7'-tetrabromo-4,5,6,7-tetrachloro-3',6'-dihydroxy-, disodium salt (18472-87-2) [<4%] TSCA

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level

California Proposition 65, Not Applicable

OTHER INFORMATION

BE SAFE: READ OUR PRODUCT SAFETY INFORMATION AND PASS IT ON. Product liability law requires it. The information provided in this Material Safety Data Sheet has been obtained from

16

current sources believed to be reliable. The manufacturer provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein. This information is offered for your information, consideration and investigation. You should satisfy yourself that you have all current data relevant to your particular use.

Revision Date: 10/22/2018